

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3945)

Set dogwood post 3 ft. long & 3" sq. from which a
Laurel, 12" dia., bears S.25°W., 16 lks.
Laurel, 12" dia., bears N.70°E., 43 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13774-5)

Point for the ¼ sec. cor. of secs. 14 & 23, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 22" in the ground with brass cap marked:

T25S R8W
¼ S 14
 S 23
 1965

from which

A fir, 14" dia., bears N.56°E., 19½ lks., mkd: ¼ S14 BT.
A fir, 13" dia., bears S.22°W., 20 lks., mkd: ¼ S23 BT.