

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3946-7)

Set for ¼ post a hemlock 3 ft. long & 3" sq. from which a
Hemlock, 10" dia., bears S.20°E., 25 lks.
Fir, 30" dia., bears N.20°E., 29 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13777)

Point for the ¼ sec. cor. of secs. 11 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 22" in the ground with brass cap marked:

T25S R8W
¼ $\frac{S\ 11}{S\ 14}$
1965

from which

A fir, 12" dia., bears N.14½°W., 24 lks., mkd: ¼ S11 BT.
A fir, 9" dia., bears S.11°W., 48 lks., mkd: ¼ S14 BT.

Howard Johnstone - For: Roseburg Lbr. Co. - 9/2/1983 - M94-76

Found - 1965 cadastral brass cap
16" hemlock (fir) N.14½°W., 15.8 ft. healed.
12" fir, S.11°W., 31.7 ft. down.
New BT - 17" hemlock, S.16°W., 15.8 ft.