

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3948)

-----  
Set fir ¼ post 3 ft. long 3" sq. from which  
A laurel, 14" dia., bears S.30°W., 9 lks.  
A laurel, 12" dia., bears N.15°W., 15 lks.

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO recs. Vol. 42 Page(s) 16444)

-----  
Point for the ¼ sec. cor. of secs. 2 & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground with brass cap marked:

T25S R8W  
¼     S 2  
       S 11  
1979

from which  
A grand fir, 8" dia., bears N.45°E., 29 lks., mkd: ¼ S2 BT  
A fir, 8" dia., bears S.6½°W., 21 lks., mkd: ¼ S11 BT.

Fd. Ok by B. Shaner - 12/7/2000 - C.S. File 65/33-19