

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T26-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3930)

Cor. to secs. 1, 2, 35 and 36, from which a
Laurel 20" dia., bears N.35°W., 14 lks. dist.
W.Fir 24" dia., bears S.50°W., 20 lks. dist.
W.Fir 36" dia., bears N.25°E., 62 lks. dist.
Chinquapin 14" dia., bears S.50°E., 21 lks. dist.

BLM resurvey by John M. Jelley and Donald Beck, Cadastral Surveyors, under Group #'s 350 & 563, surveyed Sept. 1964/July 1965 (DCSO records Vol. 33 Page(s) 13762)

The Sec. Cor., determined at the record bearing from the remains of the original BTs:

A down Fir 38" dia., bears N.25°E., 62 lks. dist., with no marks visible.

A Chinquapin snag, 17" dia., bears S.50°E., 21 lks. dist., with no marks visible on opened blaze.

A Fir snag, 40" dia., bears S.50°W., 22 lks. dist., 20 lks. to face, with illegible scribe marks visible on a bark blaze. (Rec. 20 lks.)

A Madrone 22" dia., bears N.35°W., 14 lks. dist., with no marks remaining on an open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 25	S R 8 W
S 35	S 36
S 2	S 1
T 26	S R 8 W

1964

from which new bearing trees:

A Fir 17" dia., bears N.38°E., 42 lks. dist. mkd. T25S R8W S36 BT.

A Fir 16" dia., bears S.84¼°E., 57 lks. dist. mkd. T26S R8W S1 BT.

A Fir 8" dia., bears S.37½°W., 84 lks. dist. mkd. T26S R8W S2 BT.

A Fir 8" dia., bears N.30°W., 75 lks. dist. mkd. T25S R8W S35 BT.

BLM resurvey by Peter Peterson and Daniel Berry, Cadastral Surveyors under Group #739, surveyed May/July 1971 - (DCSO records Vol. 37 Page(s) 15208)

The Sec. Cor., monumented with an iron post 2½" dia., firmly set, protruding 6" above ground, with brass cap mkd. in 1964, (Cont. Next Page)

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T26-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees:
A root hole bears N.25°E., 62 lks. dist., with a down Fir alongside, 38" dia., no marks remaining.
A Chinquapin snag 17" dia., bears S.50°E., 21 lks. dist., with opened and decayed blaze.
A Fir snag 40" dia., bears S.50°W., 22 lks. dist. with fragmentary scribe marks visible on bark blaze.
A Madrone 22" dia., bears N.35°W., 14 lks. dist. no marks visible.
and bearing trees mkd. by Jelley in 1964
A Fir 18" dia., bears N.38°E., 42 lks. dist. with healed blaze.
A Fir 18" dia., bears S.84¼°E., 57 lks. dist., with healed blaze.
A Fir 10" dia., bears S.37½°W., 84 lks. dist., with healed blaze.
A Fir stump 8" dia., bears N.30°W., 75 lks. dist., with healed blaze.
and a new bearing tree:
A Fir 25" dia., bears N.44°W., 50 lks. dist., mkd. T25S R8W S35 BT.

Survey by Mark Smalley - For: Roseburg Forest Products - April 22, 1996 - C.S. File 65/8-5

Found - 1964 Cadastral brass cap/iron pipe.
22" dia. Fir, N.38°E., 42 lks., good condition, healed face.
21" dia. Fir, S.84¼°E., 57 lks., good condition, healed face.
New BTs- 8" dia. Fir, N.10°W., 30.0 ft. scribed "S35 BT"
6" dia. Hemlock, S.71°W., 18.9 ft. scribed "S2 BT"

Brent Knapp - Crew: N. Fromdahl, J. Ogden, & W. Keady - 5/1/2023 - C.S. File 65/111-57

Condition report
Found - Brass Cap (properly mkd)
25" Fir, N.38°E., 27.7'; Healed scar & tag
23" Fir, S.84¼°E., 37.6'; Healed scar & tag
17" Fir, N.10°W., 30.0'; Healed scar & tag
9" Hemlock, S.71°W., 18.9'; Healed scar & tag
Rotten stump, N.44°W., 33'
Note - 15°E Compass Declination

continued next page

2

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T26-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 5/9/2024 - C.S. File 67/57-56

Reported as found ok

Found - brass cap

25" D.Fir N.38°E., 27.7 ft., healed scar & tag.

23" D.Fir S.84¼°E., 37.6 ft. healed scar & tag.

17" D.Fir now singed, sawn 18"x1½' stump, N.10°W.,
30.0 ft. healed scar & tag.

Note - Compass decl. 14½°E.

Oregon Coordinate Reference System

Cottage Grove - Canyonville Zone

186752.7389 N 91900.8510