TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3936)

Made a fir post 4 ft. long & 4" sq. & set for cor from which:
Fir, 36" dia., bears S.40°E., 14 lks.
Fir, 10" dia., bears N.25°W., 33 lks.
Fir, 6" dia., bears N.50°E., 23 lks.
Hemlock, 10" dia., bears S.10°W., 16 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13761)

Point for the cor. of secs. 25, 26, 35 & 36, at proportionate dist; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap marked:

T25S R8W
S 26 | S25
S 35 | S 36
1964

from which
A hemlock, 22" dia., bears N.14¾°E., 20 lks., mkd: T25S R8W S25 BT.
A fir, 7" dia. bears S.67½°E. 43 lks. mkd: T25S R8W S36 BT
A fir, 28" dia. bears S.70°W. 14 lks. mkd: T25S R8W S26 BT
A fir, 28" dia. bears N.70°W. 14 lks. mkd: T25S R8W S26 BT

Mark Smalley - For: Roseburg Forest Products - April 22, 1996 - C.S. 65/8-3

Found - IPBC Cadastral 1964
28" dia. Fir, bears N.70°W., 9.2' down.
22" dia. Hemlock, bears N.14¾°E., 13.2' good cond. - healed face.
8" dia. Fir, bears S.67½°E., 28.4', snag scribe vis.
New BTs- 6" dia. Fir, bears N.39°W., 45.4', scribed "S26 BT"
8" dia. Cedar, bears S.50°E., 20.2', scribed"S36 BT"
4" dia Hemlock, bears S.54°W. 16.9' scribed "S35 BT"