

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3937)

Set ¼ sec. post 3 ft. long, 3" sq. from which
A hemlock, 16" dia., bears S.88°E., 25 lks.
A fir, 25" dia., bears N.80°W., 15 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13763)

The ¼ sec. cor. of secs. 25 & 26, determined at record bearing & dist. from the orig. NW BT:
A down fir, 35" dia., bears N.80°W., 15 lks., mkd: 4 S on a bark blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T25S R8W
¼
S 26|S 25
1964

from which new BTs
A hemlock, 7" dia., bears N.75½°E., 23 lks., mkd: ¼ S25 BT
A hemlock, 8" dia., bears S.31¾°W., 27 lks., mkd: ¼ S26 BT

FD. brass cap & 2 BTs by D. Edwards M145-60 - Oct. 2004