

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3937)

-----  
Cor. to secs. 23, 24, 25, & 26  
Set post 4 ft. long & 4" sq. from which  
A fir, 30" dia., bears S.5°W., 7 lks.  
A chincapin, 12" dia., bears S.88°E., 3 lks.  
A hemlock, 18" dia., bears N.45°E., 42 lks.  
A fir, 28" dia., bears N.68°W., 38 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13763-4)

-----  
Point for the cor. of secs. 23, 24, 25, & 26 at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 23" in the ground, with brass cap marked:

T25S R8W  
S 23 | S 24  
S 26 | S 25  
1965

from which  
A fir, 17" dia., bears N.71½°E., 53 lks., mkd: T25S R8W S24 BT.  
A fir, 8" dia. bears S.71°W., 49 lks. mkd: T25S R8W S26 BT  
A hemlock, 19" dia., bears S.24¼°E., 5½ lks., mkd: T25S R8W S25 BT.  
A fir, 33" dia. bears N.51½°W. 8 lks. mkd: T25S R8W S23 BT

FD. brass cap & 3 BTs by D. Edwards M145-60 - Oct. 2004