TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3938)

Set ¼ post 3 ft. long, 3" sq. for cor. from which
A W.Fir, 12" dia., bears N.50°E., 17 lks.
A W.Fir, 10" dia., bears S.20°W., 25 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13765)

Point for the ¼ sec. cor. of secs. 23 & 24, at proportionate dist; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked: T25S R8W

¼
S 23| S24
1965

from which
A fir, 22" dia., bears S.42½°E., 23 lks., mkd: ¼ S24 BT.
A fir, 13" dia., bears N.88¼°W., 25 lks., mkd: ¼ S23 BT.

U.S. BLM, by Bruce A. Shaner - Feb. 5, 1973 - M49-13

Found - 1965 Cadastral brass cap.
28" W.Fir, bears S.42½°E., 15.2 ft.
14" W.Fir, now blown down, bears N.88½°W., 16.5 ft.
New BTs- 10" D.Fir, scribed "¼ S23 BT" bears S.40½°W. 25.6 ft

---