

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3938)

-----  
Cor. to secs. 13, 14, 23, & 24 at which  
I set a post 4' long & 4" sq. firmly in the ground from which  
A maple, 8" dia., bears S.50°W., 9 lks.  
A fir, 40" dia., bears N.60°W., 4 lks.  
A fir, 24" dia., bears N.30°E., 25 lks.  
A fir, 30" dia., bears S.80°E., 40 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13765-6)

-----  
The cor. of secs. 13, 14, 23, & 24, determined at rec. bearing & dist. from the remains of the orig. BTs:  
A down fir, 36" dia., bears N.30°E., 25 lks., no marks remaining on burned bark.  
A fir, 37" dia. bears S.80°E., 40 lks., with old axe marks on decaying bark.  
A fir, 64" dia, bears N.60°W., 4 lks. no marks remaining on burned bark.

At the corner point  
Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap marked:  
T25S R8W  
S 14|S 13  
S 23|S 24  
-----  
1964

from which new BTs  
A fir, 23" dia. bears N.14°E. 75 lks. mkd: T25S R8W S13 BT  
A cedar, 15" dia., bears S.43°E., 123 lks., mkd: T25S R8W S24 BT.  
A fir, 6" dia. bears S.7¼°W., 57 lks. mkd: T25S R8W S23 BT  
A hemlock, 16" dia., bears N.79½°W., 84 lks., mkd: T25S R8W S14 BT.