TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3939)

Set ¼ post 3 ft. long & 4" sq. from which a
Fir, 10" dia., bears S.30°E., 9 lks.
Fir, 12" dia., bears N.80°W., 27 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13767-8)

Point for the ¼ sec. cor. of secs. 13 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground with brass cap marked: T25S R8W

¼
S 14 | S 13
1964

from which
A fir, 14" dia., bears N.45°E., 38 lks., mkd: ¼ S13 BT.
A fir, 22" dia., bears S.21¾°W., 6 lks., mkd: ¼ S14 BT.

David Edwards - 6/25/2024 - C.S. File 65/113-41

Found - 1964 BLM standard brass capped iron pipe.
A 19" dia. Fir w/healed blaze bears N.45°E., 25.1'
The Fir S.21¾°W., is down.
New - A 24" dia. Fir scribed "¼ S14 BT" bears S.31°W., 43.2'
5.5 foot steel posts are set 2' North and 2' South.
Note - Compass decl. 15°E.