

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3940)

Cor to secs. 1, 2, 11, & 12
Set cedar post 4 ft. long & 4" sq. from which
 Fir, 24" dia., bears S.40°W., 85 lks.
 W.Fir, 24" dia., bears N.65°W., 95 lks.
 Fir, 36" dia., bears S.48°E., 85 lks.
 W.Fir, 30" dia., bears N.60°E., 190 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13769-70)

The cor. of secs. 1, 2, 11, & 12, determined at rec. dist. from the remaining orig. BTs:

 A fir, 53" dia., bears S.20°E., 85 lks., mkd: T25S R8W S12
 BT on a bark blaze. (Rec. S.48°E.)
 A fir, 45" dia., bears S.60°W., 85 lks., mkd: T25S R8W on
 decaying bark blaze. (S.40°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

 T25S R8W
 S 2 | S 1
 S 11 | S 12
 1964

from which new BTs

 A fir, 22" dia. bears N.42°E., 63 lks. mkd: T25S R8W S1 BT
 A fir, 22" dia. bears S.71°E., 7 lks. mkd: T25S R8W S12 BT
 A fir, 8" dia. bears S.57½°W. 44 lks. mkd: T25S R8W S11 BT
 A fir, 15" dia. bears N.61°W., 50 lks. mkd: T25S R8W S2 BT

Fd. & used on BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16440-1)