TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3942)

Set fir ¼ post 3 ft. long & 3" sq. from which
A W.Fir, 8" dia., bears N.50°E., 9 lks.
A fir, 24" dia., bears N.80°W., 15 lks.

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16441-2)

Point for the ¼ sec. cor. of secs. 1 & 2, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground with brass cap marked: T25S R8W

¼
S 2 | S 1
1978

from which
A fir, 9" dia., bears S.86½°E., 25 lks., mkd: ¼ S1 BT.
A fir, 6" dia., bears S.89°W., 30½ lks., mkd: ¼ S2 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 4/9/2019 (Filed 11/18/2021) - C.S. File 67/50-24

Found - A 3¼" BLM brass cap marked, as previously described, on a 2" I.D. iron pipe set plumb in an 18" dia., field poured concrete collar projecting 1" above ground and conc collar.
No evidence OBTs found.
A 24" dia., G.Fir with a FHSB; bears S.86½°E., 16.5 ft. (as per record) 1978 BLM
A 23" dia., D.Fir with a FHSB; bears S.89°W., 20.1 ft. (as per record) 1978 BLM
Green and white "T" post north 2.0 ft.
New - 9" dia., G.Fir, scribed "¼ S2" "CSBT" on a double blaze; bears S.26°W., 29.0 ft.
17" dia., D.Fir, scribed "¼ S2" "CSBT" on a double blaze; bears N.41°W., 45.3 ft.
Note - Compass decl. 14¾°E.