

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T24-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3294)

Set a Fir post 3 ft. long, 5" dia., 18" in ground for the cor. to secs. 35 and 36, from which
A Fir 12" dia., bears N.40°E., 15 lks. dist.
A Fir 6" dia., bears S.65°E., 17 lks. dist.
A Fir 40" dia., bears S.5°W., 20 lks. dist.
A Fir 48" dia., bears N.45°W., 23 lks. dist.

Fd. and used in GLO Survey by - A. R. and S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 8 Page(s) 3302)

Fd. and used in GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3315)

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - May 6, 1958 - C.S. File 49/84-4

Found - Orig. 40" now 40" Fir snag, S.5°W., 13.2 ft., shows faint but clear bark scribing "S2 R8W BT".
Rotted base of large Fir that checks bearing and distance for NW. BT.
Orig. NE. BT down, checks for bearing and distance.
Set Brass cap at cor. mkd: County Surveyors Office
S 35 | S 36 T 24 S
S 2 | S 1 T 25 S R8W
1958

New BTs- 30" Cedar bears N.38°W., 24.9 ft. scribed S35 T24S R8W CS BT.
7" W. Fir bears S.67°W., 12.8 ft. scribed S2 T25S R8W CS BT.
11" R. Fir bears N.65½°E., 53.3 ft. scribed S36 T24S R8W CS BT.
24" R. Fir bears S.58½°E., 63.0 ft. scribed S1 T25S R8W CS BT.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy - Mike Stone, crew - April 1965 - C.S. File 49/84-14

Found - 30" Cedar now snag, N.38°W., 24.9 ft., full scribing visible.
11" R. Fir N.65½°E., 53.3 ft., scribing visible.
DCSO 1958 brass cap at corner.

(Cont. Next Page)

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T24-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 7" D.Fir N.63°W., 22.3 ft. mkd. T24S R8W S35 CS BT. 5" W.Fir S.35°W., 20.3 ft. mkd. T25S R8W S2 CS BT. 8" D.Fir S.77°E., 10.5 ft. mkd. T25S R8W S1 CS BT.
Fd. OK, May 16, 1971 by DCSO, V. Tracy - C.S. File 54/55-22
Fd., used and described in BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16431)
Fd. and used in BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1241, Surveyed April/May 1986 - (DCSO records Vol. 47 Page(s) 18118-19)
Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/27/2019 (Filed 11/18/2021) - C.S. File 67/50-19 ----- Found - 1958 DCSO 2½" dia., brass cap (properly mkd) on a 1" I.D. iron pipe set plumb, proj. 9" A fallen & rotted approx. 25" dia. Fir with a previously opened blaze; roothole of which bears N.40°E., 9.9 ft. (As per rec) OBT A 32" dia., 12 ft. tall rotted fir snag with now illegible bark scribing; bears S.5°W., 13.2 ft. (as per rec) OBT From the 1958 DCSO renewal NW and SW new BTs now rootholes fd near record B & D The NE BT is now a 24" dia., D.Fir with a FHSB; bears N.65½°E., 53.3 ft. (as per record) 1958 A 24" dia., D.Fir with a FHSB; bears S.77°E., 10.5 ft. (as per rec) 1965 A rotted 18" dia., 3½" D.Fir snag is opened to find all of scribing as described. This snag bears S.35°W., 20.3 ft. (as per rec) 1965 A 19" dia., D.Fir with a FHSB; bears N.63°W., 22.3 ft. (as per rec) 1965 An alum. post fd 0.5 ft north New - A 7" G.Fir scribed "X" "CS BT" on a high-low blaze; bears N.51½°E., 10.9 ft. A 7" D.Fir scribed "X" "CS BT" on a high-low blaze; bears S.37¼°W., 42.1 ft.