

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3936)

Set fir post for 1/4 sec. cor. 3 ft. long & 3" sq. from which:
Fir, 18" dia., bears N.80°W., 16 lks.
Fir, 18" dia., bears S.20°E., 11 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13761)

The 1/4 sec. cor. of secs. 25 & 36, determined at record bearing & dist. from the remains of the orig. NW BT:
A fir snag, 21" dia., bears N.80°W., 16 lks., mkd: 1/4 S BT on a bark blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 23" in the ground, with brass cap marked:
T25S R8W
1/4 S 25
S 36
1964

from which new BTs
A fir, 13" dia., bears N.50 3/4°E., 56 lks., mkd: 1/4 S25 BT.
A fir, 21" dia., bears S.49 1/4°E., 28 lks., mkd: 1/4 S36 BT.

Mark Smalley - for: Roseburg Forest Products - April 22, 1996 - C.S. 65/8-4

Found - IPBC Cadastral 1964
20" dia. Fir, bears N.80°W., 10.6' snag.
34" dia. Fir, bears N.45°E., 9.2' good cond.- healed face.
18" dia. Hemlock, bears N.58 3/4°E., 56 lks. good cond. healed face.
24" dia. Fir, bears S.49 1/2°E., 18.5' good cond - healed face.
New BTs- W.Fir, bears N.59°W., 68.9' scribed "1/4 S BT"