

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated
May 26, 1881 (DCSO records Vol. 9 Page(s) 3938)

Set post 3 ft. long & 3" sq. for ¼ sec. cor. from which
A fir, 36" dia., bears S.20°E., 36 lks.
A fir, 12" dia., bears N.75°W., 38 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley,
Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept.
1964/July 1965 - (DCSO records 33 Page(s) 13764)

Point for the ¼ sec. cor. of secs. 24 & 25, at proportionate
distance; there is no remaining evidence of the orig. corner.
Set an iron post, 28 long, 2½" dia., 24" in the ground with
brass cap marked:

T25S R8W
¼ S 24
 S 25
1965

from which

A fir, 10" dia., bears N.17½°W., 24 lks., mkd: ¼ S24 BT.
A fir, 10" dia., bears S.36°W., 26 lks., mkd: ¼ S25 BT.