

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3939)

Set a fir post for ¼ sec. cor. 3 ft. long & 3" sq. from which
Fir, 12" dia., bears N.10°W., 14 lks.
Fir, 10" dia., bears S.75°E., 9 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13766-7)

Point for the ¼ sec. cor. of secs. 13 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 22" in the ground with brass cap marked:

T25S R8W
¼ S 13
 S 24
 1964

from which

A fir, 22" dia., bears N.14¼°E., 51 lks., mkd: ¼ S13 BT.
A fir, 18" dia., bears S.50°E., 45 lks., mkd: ¼ S24 BT.