

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3940)  
-----  
Set post 3 ft. long & 3" sq. for 1/4 sec. cor.  
    A fir, 8" dia., bears S.5°W., 28 lks.  
    A fir, 12" dia., bears N.3°W., 16 lks.

Claude Kerr - July 1955 - C.S. File 42/11  
-----  
Set a stake from orig. BT - now a 35" D.Fir bearing N.3°W., 16 lks.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy - Mike Stone- Oct. 1962 - C.S. File ~~49/76~~ 49/88-8 (6/1/2022)  
-----  
Found - Square cedar stake set by Kerr, 1955  
    34" Fir N.3°W., 10.6 ft. (slope dist.) Faint trace of old axe face & old bark scribing, portions widely separated by growth of tree & subsequent splitting of old bark surface, marks illegible now, but unmistakable scribe marks.  
    30" Fir S.5°E., (not S.5°W.) 18.5 ft. (slope dist.) Entire old north face destroyed by old injury, no marks found.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T25S R8W OFFICE 1962 1/4 S12/S13  
Note - Kerr's stake is 1 ft. south of corner.  
New BTs- 21" D.Fir N.76°E., 11.3 ft. mkd: 1/4 S12 CS BT.  
          9" D.Fir S.75°E., 32.2 ft. mkd: 1/4 S13 CS BT.  
Corner lies on steep south slope.