

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3941)

-----  
Set fir post 3 ft. long & 3" sq. for ¼ sec. cor. from which  
A maple, 12" dia., bears S.55°W., 25 lks.  
A W.Fir, 8" dia., bears S.45°E., 30 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13771)

-----  
Point for the ¼ sec. cor. of secs. 1 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 22" in the ground with brass cap marked:  
T25S R8W  
¼     S     1  
          S 12  
          1965

from which  
An Alder, 14" dia., bears N.73°W., 33 lks., mkd: ¼ S1 BT.  
A fir, 7" dia., bears S.37¼°E., 41 lks., mkd: ¼ S12 BT.