

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 25; & 30 of T. 25-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under Contract #202, dated Mar. 11, 1874 (DCSO records, Volume 9 Page 3890)

-----

Set Cedar post for ¼ sec. cor., from which  
A Laurel 10" dia., bears N.82°E., 36 lks. dist.  
A Laurel 24" dia., bears N.32°W., 33 lks. dist.

---

A.R. & S.C. Flint, GLO survey, 1881, found post & BTs.  
(DCSO records, Vol. 9 Page 3897)

---

BLM resurvey by Beck & Jelley, Group #563, Survey 1964  
(DCSO records, Volume 33 Page 13740)

-----

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set a Iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 1 ft. base to top, with brass cap mkd:

T 25 S  
R 8 W ¼ R 7 W  
S 25 | S 30  
1964

from which  
A Fir 8" dia., bears N.76°E., 11 lks., mkd. ¼ S30 BT.

---

Ronald Geisler, LS 1988 - For: Champian International Corp. - April/June 1983 - M 94-31

-----

1/4 Cor. Secs. 25 & 30 T25-7  
Found - 1964 BLM BCIP & the following accessories:  
18" Fir, bears S.34°W., 8.5' (no record found)  
13" Fir, bears N.70°E., 6.4' (rec. = N.76°E., 7.3')  
Both BTs have closed faces.

---

Fd. BC by J Terrel 6/2024 - M185-12

---

1