

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - A.R. & S.C. Flint, under Contract #392 dated  
May 26, 1881 (DCSO records, Vol. 9 Page 3899)

-----  
Set fir ¼ post, Secs. 24 and 19, 3 ft. long 3" sq., from which  
A Cedar 20" dia., bears S.80°W., 22 lks. dist.  
A Cedar 18" dia., bears N.53°E., 18 lks. dist.

BLM resurvey by Beck & Jelley, Group #563, Survey, 1964  
(DCSO records, Volume 33 Page 13742)

-----  
Point for the ¼ sec. cor. of sec. 24 only, at proportionate  
distance; there is no remaining evidence of the original  
corner. Set a Iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd:

T 25 S |  
R 8 W |  
¼ S 24 |  
1964

from which

A Fir 7" dia., bears S.44°W., 70 lks. mkd. ¼ S24 BT.  
A Madrone 8" dia., bears N.41½°W., 29 lks. mkd. ¼ S24 BT.

Kris DeGroot - For: Roseburg Resources - 2/2002 - M 137-49

-----  
Found - 1964 BLM BCIP, firmly set, projecting 3" above the  
ground, stamped:

T 25 S |  
R 8 W |  
¼ S 24 |  
1964

From which BTs by Beck & Jelley in 1964:

9" high stumped D.Fir bears S.47½°W., 47.2 ft. with  
a healed blaze (rec. S.44°W., 70 lks.)

10" Madrone bears N.34°W., 19.5 ft. with a healed  
face (rec. N.41½°W., 29 lks.)

New BT - 15" Madrone bears S.1°W., 39.4 ft. bark scribed "¼  
S24 BT" (Double blazed face with a brass  
washer stamped "PLS 1941" nailed into the lower  
blaze. Bearing is taken to the center of the  
tree at the root crown and the distance is  
measured to a nail in the root crown at the  
side & center of the tree. Red band painted  
around the tree & the blazed face painted red  
& BT sign nail to tree.)