

PRIMARY CORNER DESCRIPTION Cor. for Secs. 13 & 24 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - A.R. & S.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Volume 9 Page 3899)

Set Fir post, 4 ft. long, 4" sq., from which
A Fir 16" dia., bears N.25°E., 5 lks. dist.
A Fir 14" dia., bears S.82°E., 19 lks. dist.
A Fir 36" dia., bears S.40°W., 20 lks. dist.
A Fir 14" dia., bears N.85°W., 33 lks. dist.

BLM resurvey by Beck & Jelley, Group #563, Survey, 1964
(DCSO records, Volume 33 Pages 13742-43)

The cor. of secs. 13 and 24 only, determined at record bearing and distance from the remaining original bearing trees:

A down Fir 25" dia., bears S.82°E., 19 lks. dist., no marks visible.

A W.Fir snag 16" dia., bears N.85°W., 33 lks. dist., with scribe marks T25S R8W BT, visible on bark blaze.

At the corner point: Set a Iron post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd: T 25 S

R 8 W		R 7 W
S 13		S 18
S 24		
1964		

from which new bearing trees

A W.Fir 27" dia., bears S.75°W., 50½ lks. mkd. T25S R8W S24 BT.

A Fir 45" dia. bears N.35°W. 50 lks. mkd. T25S R8W S13 BT

Kris DeGroot - For: Roseburg Resources - 2/2002 - M 137-49

Found - 1964 BLM BCIP, firmly set, projecting 3" above the ground, (properly mkd.)

From which Orig. BTs:

A root hole bears N.88°E. 10.3 ft. w/uprooted rotted 14" D.Fir along side (rec. S.82°E., 19 lks.)

16" W.Fir snag bears N.83¼°W., 21.4 ft. No visible marks (rec. N.85°W., 33 lks.)

From which BTs by Beck & Jelley in 1964:

45" Fir stump bears S.74¼°W., 31.9 ft. no visible marks (rec. S.75°W., 50½ lks.)

A root hole bears N.25¾°W., 33.2 ft. with a uprooted 45" D.Fir alongside. (Rec. N.35°W., 50 lks.)

And BTs by Smalley in 2001

10" D.Fir bears S.47°W., 18.0 ft. scribed "S13 BT" with brass washer stamped "LS 2354"

continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Cor. for Secs. 13 & 24 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" D.Fir bears N.78°W., 17.5 ft. scribed "S13 BT" with brass washer stamped "LS 2354"

Note - By agreement, new BTs at this corner was scribed by Mark Smalley PLS 2354 of Roseburg Resources, are being entered into the Douglas County Surveyors records by this survey, in lieu of separate corner reports being filed by Smalley on these corners.