

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - A.R. & S.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Volume 9 Page 3899)

Set Cedar ¼ post, 3 ft. long, 3" sq. on the N slope of canyon, from which

A Hemlock 10" dia., bears N.42°E., 11 lks. dist.

A Hemlock 8" dia., bears S.85°W., 5 lks. dist.

BLM resurvey by Beck & Jelley, Group # 563, Survey, 1964 (DCSO records, Volume 33 Pages 13743-44)

Point for the ¼ sec. cor. of sec. 13 only, at proportionate distance; there is no remaining evidence of the original corner.

Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 25 S |
R 8 W |
¼ S 13 |
1964

from which

A Cedar 28" dia., bears S.61°W., 57 lks. dist.
mkd. ¼ S13 BT.

A Hemlock 12" dia., bears N.49°W., 54 lks. dist.
mkd. ¼ S13 BT.

Found OK by K. DeGroot, Feb. 2002 - M137-49