

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, T25-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - A.R. & S.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Volume 9 Page 3900)

Set Hemlock post, 4 ft. long, 4" sq. firmly in the ground, from which

- A Fir 8" dia., bears N.50°E., 27 lks. dist.
- A Fir 48" dia., bears S.85°W., 12 lks. dist.
- A Fir 8" dia., bears N.5°W., 11 lks. dist.
- A Fir 30" dia., bears S.65°E., 27 lks. dist.

GLO survey by William P. Heydon, under Contract #656, dated May 21, 1896 (DCSO records, Volume 9 Page 3911)

Intersect W. bdy of Tp. 10.00 chs. S of cor. to secs. 7, 12, 13 and 18, which is a Hemlock post firmly set in the ground marked and witnesses as described by the Surveyor General. I obliterate marks on post and bearing trees referring to secs. in R. 7 W.

At point of intersection, set a Fir post, 3 ft. long, 4" sq., 24" in the ground for closing corner for Secs. 7 and 18 mkd. C.C. T25S R7W on E. S7 on N. and S18 on S faces, with 4 grooves on S and 2 grooves on N faces, from which

- A Fir 18" dia., bears N.70°E., 42 lks. marked CS T25S R7W S7 BT.
- A Fir 10" dia., bears S.44°E., 50 lks. marked CC T25S R7W S18 BT.

BLM resurvey by James Jelley, under Group # 563 - Survey, 1964 (DCSO records, Volume 33 Page 13744)

Point for the closing cor. of secs. 7 & 18, at proportionate distance; there is no remaining evidence of the original cor. Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 25 S		
R 8 W	R 7 W	
	S 7	CC
S 13	S 18	
1964		

from which

- A Fir 54" dia., bears N.23½°E., 38 lks. mkd. T25S R7W S7 CC BT.
- A Fir 40" dia., bears S.59°E., 51 lks. mkd. T25S R7W S18 CC BT.

Cor. falls on a spur, slopes S.60°W.; desc. 190 ft. over broken NW. slope.

continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 700471

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, T25-7

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Kris DeGroot - For: Roseburg Resources - 2/2002 - M 137-49

Found - 1964 BLM BCIP, firmly set, projecting 3" above the ground, (properly mkd.)

From which BTs by Beck & Jelley in 1964:

36" high stumped D.Fir bears S.56°E., 33.5 ft. with scribe marks "T25S R7W S18 CC BT" visible (Rec. S.59°E., 33.7 ft.)

And BTs by Smalley in 2001:

11" D.Fir bears N.82°E., 2.8 ft. scribed "S18 BT" w/brass washer stamped "LS 2354"

16" W.Fir bears N.24½°E., 11.9 ft. scribed "S7 BT" w/brass washer stamped "LS 2354"

20" W.Fir bears N.59°W., 37.4 ft. scribed S7 BT" w/brass washer stamped "LS 2354"

Note - By agreement, new BTs at this corner was scribed by Mark Smalley PLS 2354 of Roseburg Resources, are being entered into the Douglas County Surveyors records by this survey, in lieu of separate corner reports being filed by Smalley on these corners.