

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 700521

PRIMARY CORNER DESCRIPTION W.C. East bdy. Sec. 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, Contract #73 dated June 8, 1857 (DCSO records, Vol. 9 Page 3874)

-----  
At 58.95 chs. south, marked a Maple 6" dia., from which  
A Maple 12" dia., bears West 12 lks.  
A Fir 30" dia., bears S.80°E., 10 lks.

Claude Kerr, 1954, C.S. File 41/316

-----  
Found - Orig. Fir BT, now 50" dia., bearing S.80°E., 10 lks.  
(marking still visible).  
Reset the Witness Corner, from this BT, setting 4"x4" stake,  
which I scribe W.C. on the East and West faces, & 58.75 chs.  
S. on the North face.  
New BT - 14" Red Cedar bearing N.55°W., 19 ft. and marked  
W.C. S12 BT.  
The ¼ cor. for 7 & 12 can be seen from the W.C. at 58.95 chs.  
South. The correct variation between these corners is  
20°20'E.

Doug. County Surveyors Office - Milo Godfrey; Mike Stone;  
Oct. 24, 1962 - C.S. File 49/76-22

-----  
Found - Stake set by Kerr, 1954, fallen over & downhill from  
corner.  
18" R.Cedar N.55°W., 19.0 ft. Kerr's scribing still  
visible in partly healed over scars.  
50" Fir S.80°E., 6.6 ft. Old axe blazes visible in  
bark, faint traces of possible scribing visible  
in scars.  
Set Brass cap at cor. mkd: County Surveyor's Office, 1962  
T25S R8W W.C. S12|S7 R7W  
New BT - 6" Myrtle S.50°E., 16.0 ft. mkd: T25S R7W W.C.  
S7 CS BT.  
Corner lies on precipitous North slope, approx. 300 ft. South  
of River.

BLM resurvey by James Jelley, under Group #563, Survey, 1964  
(DCSO records, Volume 33 Page 13745)

-----  
The orig. Witness Point of secs. 7 & 12, established by  
Hathorn in 1857; recorded & remonumented by C.Kerr in 1954,  
with a wooden stake 4" sq., 36" above the ground, loosely set,  
mkd. WC 7 WC 12, 5895 chs., subsequently remonumented by Milo  
(Cont. Next Page)

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 700521

PRIMARY CORNER DESCRIPTION Wit. Cor., East Bdy, Sec. 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Godfrey, in 1962, with a 1" I.P. firmly set, 8" above ground, with brass cap.  
from which the remaining orig. BTs  
    A Fir 52" dia., bears S.80°E., 12½ lks. dist., with old bark blaze. (Rec. 10 lks.)  
and a bearing tree marked by Kerr  
    A Cedar 17" dia., bears N.55°W., 28½ lks. dist., with scribe marks WC S12 BT visible on partially healed double blaze.  
and a bearing tree marked by Godfrey  
    A Myrtle 6" dia., bears S.50°E., 24½ lks. dist., mkd. T25S R7W WC S7 CS BT visible on double blaze.  
Add marks BLM 1964 to bottom of brass cap.