

TOWNSHIP 25 RANGE 09 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor. Secs. 33, 34; 3 & 4 T26-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John W. Meldrum, U.S. Deputy Surveyor, under contract #663, dated May 21, 1896 - (DCSO records Vol. 10 Page(s) 4019-20)

-----  
Set Fir post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 3, 4, 33 & 34, mkd. T25S S34 on NE.; R9W S3 on SE.; T26S S4 on SW.; and S33 on NW. faces, with 3 notches on E. and W. edges, from which

- A Cedar, 18" dia., bears N.67°E., 72 lks., mkd: T25S R9W S34 BT.
- A Fir, 24" dia., bears S.66°E., 56 lks., mkd: T26S R9W S3 BT.
- A Fir, 36" dia., bears S.70°W., 71 lks., mkd: T26S R9W S4 BT.
- A Cedar, 26" dia., bears N.40°W., 48 lks., mkd: T25S R9W S33 BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 55/155B-2 - Filed 6/17/2001

- 
- 38" Cedar stump "W" nail & tag N.65°E., 47.2 ft.
  - 36" Fir stump "W" nail & tag S.64°E., 38.1 ft.
  - 24" Hem. stump "W" nail & tag S.84½°W., 25.2 ft.
  - 36" Cedar stump "W" nail & tag N.42°W., 33.2 ft.
- This information added to the corner report on 9/26/2001.  
DCSO