

TOWNSHIP 25 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, U.S. Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 10 Page(s) 4050)

Set a fir post, 6" sq., 3 ft. long, 24" in the ground for cor. of secs. 27, 28, 33 & 34, marked T25S S27 on NE, R9W S34 on SE, S33 on SW & S28 on the NW faces, with 1 notch on S & 3 notches on the E edges, from which

A fir, 28" dia., bears N.75½°E., 54 lks., mkd: T25S R9W S27 BT.

A fir, 38" dia., bears S.50°E., 17 lks., mkd: T25S R9W S34 BT.

A fir, 24" dia., bears S.50½°W., 25 lks., mkd: T25S R9W S33 BT.

A fir, 42" dia., bears N.40¾°W., 28 lks., mkd: T25S R9W S28 BT.

Tony Hostetter - For: Weyerhaeuser Co. Co. - March 2010 - C.S. File 65/69-11

Found - 3 orig. GLO BTs.
28" Fir stump, WEYCO tag, bears N.75½°E., 35.6 ft. to center. (GLO 28" Fir N.75½°E., 54 lks)
40" Fir stump, WEYCO tag, bears S.50°E., 11.2 ft. to center. (GLO 38" Fir, S.50°E., 17 lks.)
36" Fir stump, no marks, bears N.37°E., 18.4 ft. to center. (GLO 42" Fir, N.40°45'W., 28 lks.)
Set - 5/8" rebar w/plastic cap marked "HOSTETTER LS 1975"
New BTs- 20" Fir stump, WEYCO tag & spike, bears S.70°E., 42.2 ft. to spike.
14" Fir stump, WEYCO tag & spike, bears S.78°W., 20.7 ft. to spike.
14" Fir stump, WEYCO tag & spike, bears N.28°W., 18.7 ft. to spike.

Corner location: GAMIN 60CSX GPS
43°21'32.2"N
123°45'41.8"W