

TOWNSHIP 25 RANGE 09 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION W ¼ Cor. Sec. 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles L. Campbell, U.S. Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 10 Page(s) 4051)

Marked a fir, 18" dia. for ¼ sec. cor., mkd ¼ S28 on the W & S27 on the E faces; from which
A fir, 30" dia., bears S.3¾°E., 43 lks., mkd: ¼ S BT.
A fir, 30" dia., bears N.15°W., 29 lks., mkd: ¼ S BT.

Tony Hostetter - For: Weyerhaeuser Co. - June 9, 2015 - C.S. File 65/89-52

Found - Steel "T" fence post, 2 ft out of ground. Evidently set by WEYCO but not listed in their records.
41" fir stump, face evident, listed in WEYCO records as OBT, tag & "W" nail, (GLO N.15°W., 29 lks) bears N.15°W., 18.0 ft. to center.
New BTs- 24" Fir, BT tag, bears N.40°E., 0.7 ft. to 6" spike, placed below tag.
16" Fir, BT tag, bears S.15°E., 28.3 ft to 6" spike, placed below tag.
18" Fir, BT tag, bears S.16°W., 42.4 ft to 6" spike, placed below tag.
18" Fir, BT tag, bears N.16°W., 14.2 ft to 6" spike, placed below tag.