

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W. Meldrum, U.S. Deputy Surveyor, under contract #663, dated May 21, 1896 - (DCSO records Vol. 10 Page(s) 4020-21)

Set Fir post 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 2, 3, 34 and 35, mkd. T25S S35 on NE.; R9W S2 on SE.; T26S S3 on SW.; and S34 on NW. faces, with 2 notches on E. and 4 notches on W. edges, from which
An Alder 4" dia., bears N.44°E., 25 lks. dist. mkd. T25S R9W S35 BT.
A Fir 30" dia., bears S.62°E., 55 lks. dist. mkd. T26S R9W S2 BT.
A Cedar 10" dia., bears S.23°W., 35 lks. dist. mkd. T26S R9W S3 BT.
A Fir 12" dia., bears N.43°W., 82 lks. dist. mkd. T25S R9W S34 BT.

Weyerhaeuser corner report, no surveyor's name or stamp, no date of visit - C.S. File 55/155B-1 - Filed 6/17/1970

40" DF "W" nail & tag N.43°W., 55.2 ft.
18" Hem. "W" nail & tag S.22°E., 59.6 ft.
OBT 20" Cedar "W" nail & tag S.23°W., 23.1 ft.
20" W.Fir "W" nail & tag N.52½°E., 31.5 ft.
This information added to the corner report on 9/26/2001. DCSO

Survey by Robert C. Adamek, For: Weyerhaeuser Co. - Feb. 2, 1977 - C.S. File 58/135; M 63-19

Found - Orig. 16" Cedar, bears S.23°W., 35 lks. A larger Cedar now stands between this BT and the corner.
Orig. D.Fir 48", bears N.43°W., 82 lks.
Set 3/4" Iron pipe.

Survey by Michael S. McDowell - For: Weyerhaeuser Co. - Sept. 25, 1981 - C.S. File 58/8-46

Found - 1" Iron pipe.
36" Fir, OBT, bears N.43°00'W., 55.6 ft.
28" Cedar, OBT, bears S.23°00'W., 24.2 ft.
Said corner falling on the centerline of a proposed logging spur, and with the possibility of existing accessories being obliterated by the road construction, new accessories were established as follows:
28" W.Fir scribed "BT" bears N.19°30'E., 68.2 ft.
20" Fir scribed "BT" bears S.42°30'E., 87.3 ft.
18" Cedar scribed "BT" bears S.36°00'W., 36.6 ft.