

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by Charles L. Campbell, U.S. Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 10 Page(s) 4039)

-
- Marked a hemlock, 12" dia., for cor. of secs. 22, 23, 26, & 27, marked T25S S 23 on NE, R9W S 26 on SE, S 27 on SW, S 22 on NW faces, with 2 notches on S & E edges; from which
- A hemlock, 36" dia., bears N.35½°E., 56 lks., mkd: T27S R3W S23 BT.
 - A hemlock, 12" dia., bears S.23°E., 39 lks., mkd: T27S R3W S26 BT.
 - A hemlock, 10" dia., bears S.29°W., 40 lks., mkd: T27S R3W S27 BT.
 - A hemlock, 24" dia., bears N.58¼°W., 58 lks., mkd: T27S R3W S22 BT.

Tony Hostetter - For: Weyerhaeuser Co. - Jan. 24, 2008 - C.S. File 65/63-7

-
- Unrecorded History
- Weyerhaeuser Co. records Dec. 1965
- Found - 36" Hemlock, OBT, bears N.35½°E., 37.0 ft.
24" Hemlock, OBT, bears S.23½°E., 26.1 ft.
30" Hemlock, OBT, bears S.25½°W., 23.5 ft.
3/4" Iron pipe, was set in 1983 (WEYCO record)
- January 2008
- Found - 3/4" Iron pipe, from which
30" Hemlock stump, possible face, axe marks, WEYCO tag OBT, bears S.23°E., 25.7 ft. to center.
- New BTs-
- 12" Fir, WEYCO tag & "W" nail, bears N.70°E., 16.8 ft. to "W" nail placed in root collar below tag.
 - 14" Fir WEYCO tag & "W" nail, bears S.88°E., 21.0 ft. to "W" nail placed in root collar below tag.
 - 15" Fir WEYCO tag & "W" nail, bears S.28°E., 14.1 ft. to "W" nail placed in root collar below tag.
 - 14" Fir WEYCO tag & "W" nail, bears N.30°W., 5.4 ft. to "W" nail placed in root collar below tag.