

TOWNSHIP 25 RANGE 09 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2, T26-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by John W. Meldrum, Deputy surveyor, under Contract #662, dated December 16, 1866 (DCSO records Vol. 10 Page(s) 4021)

Set a Laurel post 3 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which
A Laurel 4" dia., bears N.40°W., 10 lks. dist. mkd. 1/4 S BT
A Fir 4" dia., bears S.10°W., 45 lks. dist. mkd. 1/4 S BT.

Survey by Robert C. Adamek - For; Weyerhaeuser Co. - Feb. 2, 1977 - C.S. File 58/135; M 63-19

Found no trace of orig. corner or its accessories.
Set 3/4" Iron pipe, from which a
19" D.Fir bears N.49 1/2°W., 7.5 ft. scribed 1/4 CNR RP.
14" D.Fir bears S.22°W., 12.6 ft. scribed 1/4 CNR RP.

Tony Hostetter - For: Weyerhaeuser Co. - March 2023 - M182-21

Found - 3/4" iron pipe as set by Adamek in 1977 (M63-19).
from which:
20" Fir, face evident, WEYCO tag, bears, S.22°W.,
12.6 ft to center
New BTs- 36" Fir, marked "X", BT tag, bears, N.25°55'E., 7.7
ft to spike.
42" Fir, marked "X", BT tag, bears, S.43°47'E., 28.3
ft to spike.
10" Hemlock, marked "X", BT tag, bears; S.13°49'W.,
21.8 ft to spike.
10" Fir, marked "X", BT tag, bears; S.65°44'W., 26.4
ft to spike.