

TOWNSHIP 25 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Charles L. Campbell, Dep. Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 10 Page(s) 4042)

-----  
Set sandstone, 20x12x8" 15" in the ground, for sec. cor., marked ¼ on the N. face; from which,  
A fir, 58" dia., bears S.87½°W., 60 lks. mkd ¼ S23 BT.  
A fir, 24" dia., bears N.26½°W., 24 lks. mkd ¼ S14 BT.

Tony Hostetter - For: Weyerhaeuser Co. - Feb. 2005 - C.S. File 65/54-14

-----  
Found - ¾" iron pipe (1965 Weyerhaeuser recs. indicate that the orig. GLO stone & 2 BTs were fd., the ¾" iron pipe & 2 new BTs were set at that time) (No rec. of WEYCO corner report in DCSO, 3/28/2005)  
42" Fir stump, WEYCO tag & "W" nail, bears S.22°W., 168.3 ft. to center.  
48" Fir stump, WEYCO tag N.8°W., 45.0 ft. to center.  
New BTs- 12" Fir WEYCO tag & spike, bears N.59°E., 19.9 ft. to spike.  
10" Fir WEYCO tag & spike, bears S.70°W., 1.5 ft. to spike.  
12" Fir WEYCO tag & spike, bears N.1°E., 14.2 ft. to spike.