

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25, only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 10 Page(s) 3959)

Set sandstone 30x24x6 ins., 22" in the ground for ¼ sec. cor. mkd. ¼ on the W. face, from which
A Fir 72" dia., bears N.54 3/4°E., 67 lks. dist. mkd. ¼ S30 BT.
A Fir 60" dia., bears S.51½°W., 66 lks. dist. mkd. ¼ S25 BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3968)

The ¼ sec. cor., which is a sandstone firmly set, mkd. and witnessed as described by the Surveyor General, and which I now change to refer to sec. 25, T25S R9W only.

BLM Resurvey by James E. Jelley and Jack W. Bowder, Cadastral Surveyors, under Group #767, Surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15034)

The ¼ Sec. cor., monumented with the original sandstone, 30 x 24x6 ins., mkd. ¼ on W. face, firmly set, 18" in the ground, alongside of which, an iron pipe 1" dia., from which the remains of the original bearing trees:

A sawed Fir stump 66" dia., bears N.54 3/4°E., 67 lks. dist., with healed blaze and a nail, with "W" embossed on the head, driven into base.

A sawed Fir stump 54" dia., bears S.51½°W., 66 lks. dist., with healed blaze and a nail, with "W" embossed on the head, driven into base.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
¼ S 25
T 25 S
R 9 W
1972

from which a new bearing tree
A Dogwood 6" dia., bears S.52°W., 50 lks. dist., mkd. ¼ S25 BT.

Deposit corner stone and reset iron pipe alongside the iron post.

(Cont. Next Page)

TOWNSHIP 25 RANGE 09 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Henry R. Reppeto - For: Weyerhaeuser Co. - Feb. 6, 1976 -
C.S. File 58/90 and M 59-34

Found BLM monument with the following accessories:
66" D.Fir stump bears N.54 3/4°E., 67 lks., Orig. BT.
54" D.Fir stump bears S.51 1/2°W., 66 lks., Orig. BT.
6" stub bears S.52°W., 50 lks.