TOWNSHIP 25 RANGE 09 POINT IDENTIFIER # 700246

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 30 only, T25-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by James E. Jelley and Jack W. Bowder, Cadastral Surveyors, under Group #767, Surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15050)

The point for the ¼ sec. cor., of sec. 30 only, T25S R8W., is at midpoint latitudinally on the W. bdy. of sec. 30.
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd.
1/4 S 30
T 25 S
R 8 W
1972
from which
A sawed Fir stump 36" dia., bears S.56½°E., 54½ lks. dist. mkd. ¼ S30 BT.
A sawed Fir stump 42" dia., bears S.25°E., 82 lks. dist. mkd. ¼ S30 BT.

Survey by Henry R. Reppeto - For: Weyerhaeuser Co. - March 6, 1975 - C.S. File 58/45

Found BLM monument with the following accessories:
38" D.Fir stump, bears N.56½°W., 54.5 lks.
40" D.Fir stump, bears N.25°W., 82 lks.