

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5, 1902 - (DCSO records Vol. 10 Page(s) 3959)

-
- Set sandstone 24x12x4 ins., 18" in the ground for cor. of secs. 19, 24, 25, 30 marked with 4 notches on the N. and 2 notches on the S. edges, from which
- A Fir 50" dia., bears N.64°E., 24 lks. dist. mkd. T25S R8W S19 BT.
 - A Fir 28" dia., bears S.81 3/4°E., 11 lks. dist. mkd. T25S R8W S30 BT.
 - A Fir 64" dia., bears S.4½°W., 46 lks. dist. mkd. T25S R9W S25 BT.
 - A Fir 56" dia., bears N.80½°W., 159 lks. dist. mkd. T25S R9W S24 BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3968)

The cor. of secs. 19, 24, 25 and 30, which is a sandstone, firmly set, mkd. and witnessed as described by the Surveyor General, and which I now change to refer to secs. 24 and 25, T25S R9W only.

BLM Resurvey by James E. Jelley and Jack W. Bowder, Cadastral Surveyors, under Group #767, Surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15035)

-
- The cor. of secs. 24 and 25 only, monumented with the original sandstone, 24x12x4 ins., mkd. with 4 notches on the N. and 2 notches on the S. edges, loosely set, 5" in the ground, from which the remains of the original bearing trees:
- A Fir 55" dia., bears N.64°E., 46 lks. dist., with healed blaze. (Rec. 24 lks.)
 - A Fir 34" dia., bears S.81 3/4°E., 11 lks. dist., with healed blaze.
 - A Fir 74" dia., bears S.4½°W., 89½ lks. dist., with healed blaze. (Rec. 46 lks.)
- and a bearing tree of which I have no record:
- A Fir 40" dia., bears N.16½°W., 14 lks. dist., with healed blaze and a nail, with "W" embossed on the head, driven into base.
- At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: (Cont. Next Page)

TOWNSHIP 25 RANGE 09 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 25 S T 25 S
S 24 R 8 W
S 25 S 30
R 9 W
1972

Deposit corner stone alongside the iron post.

Henry Reppeto - For: Weyerhaeuser Co. - Feb. 6, 1976 - C.S.
File 58/90 and M 59-34

Found BLM monument with the following accessories:
55" D.Fir bears N.64°E., 46 lks., orig. BT, (Rec. 24 lks.)
34" D.Fir bears S.81 3/4°E., 11 lks., Orig. BT.
74" D.Fir bears S.4½°W., 89½ lks. Orig. BT (Rec. 46 lks.)
40" D.Fir bears N.16½°W., 14 lks.

2