

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 10 Page(s) 3964)

Set Hemlock post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S1 on the W. and S6 on the E. faces, from which

A Fir 48" dia., bears N.87½°E., 32 lks. dist. mkd. ¼ S BT

A Fir 50" dia., bears S.85°W., 29 lks. dist. mkd. ¼ S BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3970)

The ¼ cor. bet. secs. 1 and 6, which is a sandstone (instead of a Hemlock post) firmly set, mkd. ¼ on W. face, and witnessed as described by the Surveyor General, and which I now change to refer to sec. 1, T25S R9W only.

Survey by Donald Peel - For: Weyerhaeuser Co. - May 1967 - C.S. File 55/30-4

Found - GLO Survey record, sandstone, gone.

48" Fir N.87½°E., 32 lks., now Fir windfall, chopped open. Scribe visible, supposedly markings destroyed in 1911, but not so.

50" Fir S.85°W., 29 lks., now 50" Fir, closed face.

Set 4 ft. x 3/4" Pipe, 2½ ft. in ground and square post.

Re-referenced BTs with "W" nails & plates only:

50" Fir, S.84°W., 17.0 ft.

60" Fir, N.47°W., 5.3 ft.