

PRIMARY CORNER DESCRIPTION A P on E. Bdy. of Section 1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 10 Page(s) 3965)

-----  
(Intersect S. bdy. of T24S R9W, 23.54 chs. W. of the cor. of Tps. 24 & 25 S., Rs. 8 and 9 W.,) At point of intersection, I set a Fir post 8" sq., 3 ft. long, 24" in the ground for closing cor. of Tp. 25 S., Rs. 8 and 9 W. marked CC T25S on the S.; R8W S6 on the E. and R9W S1 on the W. faces with 6 grooves on the S., E., and W. faces, from which  
A Fir 36" dia., bears S.30°E., 93 lks. dist. mkd. T25S R8W S6 BT.  
A Fir 40" dia., bears S.61 3/4°W., 20 lks. dist. mkd. T25S R9W S1 BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3970)

-----  
At closing cor. for Tps. 25S., Rs. 8 and 9, which is a post, mkd. and witnessed as described by the Surveyor General.  
Note: This closing cor. is not set on the S. bdy. of sec. 36, T24S R9W. (found and retraced by me, July 20, 1911,) as reported in field notes returned by Chas Campbell, but is some distance South of same.

Survey by Donald Peel - For: Weyerhaeuser Co. - May 1967 - C.S. File 55/30

-----  
Found - GLO survey record, post, gone.  
36" Fir S.30°E., 93 lks., now 37" Fir, closed face, Not S.30°E., but S.61°E.  
40" Fir S.61°W., 20 lks., now 42" Fir, closed face, N.61°W., but S.30°W.  
From the call distances and the direction of the faces on the BTs, I would say the brgs. in the orig. field notes were reversed.  
Set 4 ft. x 3/4" pipe 3 ft. in the ground and square post.  
Re-referenced the BTs with "W" nails & plates only:  
42" Fir S.35°W., 11.7 ft.  
18" Cedar N.47°W., 12.5 ft.

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16439)

-----  
(Cont. Next Page)

TOWNSHIP 25 RANGE 09 POINT IDENTIFIER # 700667

PRIMARY CORNER DESCRIPTION A P on E. bdy. Section 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The corner established by Campbell in 1902, for the closing cor. of T25S Rs. 8 and 9 W., and changed to an angle point by Wygant in 1911, perpetuated and recorded by Peel in 1967, monumented with an iron pipe 1/4" dia., firmly set, projecting 6" above ground, with which the original bearing trees:

A Fir 40" dia., bears S.61 3/4°E., 93 lks. dist., with healed blaze. (Rec. S.30°E.)

A Fir 44" dia., bears S.30°W., 20 lks. dist. with healed blaze. (Rec. S.61 3/4°W.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron pipe, with brass cap mkd:

A P  
T 25 S  
R 8 W  
S 6  
1978

from which a new bearing tree

A Cedar 11" dia., bears N.48°E., 74 lks. dist. mkd. AP S6 BT.