

TOWNSHIP 25½ RANGE 01E POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Otto L. Draper, U.S. Transitman - Under instructions dated March 12, 1921 - (DCSO records Vol. 22 Page(s) 9237-38)

Point for the ¼ sec. cor. of sec. 31 only. Set an iron post 3 ft. long, 1" dia., 27" in the ground, for the ¼ sec. cor. of sec. 31 only, with brass cap mkd.

¼ S 31

1928

from which

A Cedar 5" dia., bears S.55°E., 16 lks. dist. mkd. ¼ S31
BT.

A Fir 20" dia., bears S.23°W., 56 lks. dist. mkd. ¼ S31
BT.

Milo E. Godfrey, Deputy - Vernon Tracy - Mike Stone - Aug. 1962 - C.S. File 52/30-11

Found - GL0 brass cap & both BTs mentioned in 1928 survey - all in good condition.

FD 10/1966 DCSO VRT, JH, & DW - 10/1966 - C.S. File 52/30-28A

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 5/13/2024 - C.S. File 67/57-58

Found - 2½" GL0 brass cap (properly mkd) on 1" ID IP up 6" in rough stone mound.

Burned-dead 14" R.Cedar S.55°E., 10.3 ft. (rec 16 lks) blaze not visible, add 3½" mag nail right side center.

Down, burned up fir S.23°W., 37.0 (rec. 56 lks) root hole and tag.

New - 41" burned, dead D.Fir S.1°W., 34.1 ft. 3½" mag nail right side center.

31" burned, dead r.Cedar N.70°W., 17.0 ft. 3½" mag nail right side center.

Note - Cor on flat ground near bottom of moderate South slope.

Burned old growth to south clear cut to North.
Compass decl. 14½°E.

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 188901.729 E 319991.659