

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3491)

-----  
Set a basalt stone 16x12x10 ins., 12" in the ground for cor. of Tps. 25 and 26 S., Rgs 1 E and 1 W., marked with 6 notches on each edge, from which  
An Alder 12" dia., bears N.33°E., 47 lks. dist. mkd. T25S R1E S31 BT.  
A Fir 60" dia., bears S.33°E., 72 lks. dist. mkd. T26S R1E S6 BT.  
A Fir 12" dia., bears S.10°W., 50 lks. dist. mkd. T26S R1W S1 BT.  
A Fir 24" dia., bears N.57°W., 80 lks. dist. mkd. T25S R1W S36 BT.  
Cor. is on a steep hillside, sloping E., 225 ft. above McKinley Creek.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9108)

-----  
The Cor. established for Tps. 25 and 26 S., Rs. 1 E. and 1 W., is a basalt stone, 18x12x8 ins., loosely set in a mound of stone, marked with 6 notches on N., E., S., and W. edges. I now change this cor. to refer to Tps. 25 S., Rs 1 E. and 1 W. only.  
RESET the basalt stone, 14" in the ground marked 25S on N.; 1E on E.; and 1W on W. face; from which  
A Fir 60" dia., bears S.36°E., 72 lks. dist., old BT, the marks on which I now destroy.  
A Fir 18" dia., bears S.11½°W., 50 lks. dist., old BT, the marks on which I now destroy.  
A Fir 30" dia., bears N.54½°W., 80 lks. dist. mkd. T25S R1W S36 BT. (Old BT)  
A Fir 8" dia., bears N.67½°E., 86 lks. dist. mkd. T25S R1E S31 BT. (New BT)  
The old bT in T25S R1E is dead and fallen.

Glenn Baughman - For: U.S. Forest Service - Sept. 1980 - C.S. File 58/229-38

-----  
Found - 18"x12"x8" basalt stone with 6 notches in the N. S. E. and W. faces. Stone was laying on top of the ground.  
A 62" D.Fir, orig. BT, with healed blaze, bears S.36°E., 47.5 ft. (Scribe marks destroyed in 1927 resurvey) (Cont. Next Page)

TOWNSHIP 25½ RANGE 01E POINT IDENTIFIER # 164200

PRIMARY CORNER DESCRIPTION Tsp Cor Sec 36 T25-1W & Sec 31 T25-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A 28" D.Fir, orig. BT, with healed blaze, bears S.11½°E., 30.0 ft. (Rec. 33.0 ft.) Scribe marks destroyed in 1927 resurvey.  
A 45" D.Fir, orig. BT, with healed blaze, bears N.54½°W., 52.8 ft.  
A 22" D.Fir, orig. BT, with healed blaze, bears N.67½°E., 56.8 ft.  
A 24" Cedar (not of record) with healed blaze, bears N.32°E., 30.1 ft.  
At the corner point, I SET a 2½" x 30" Iron pipe, 6" in the ground on bedrock in concrete, and in a 3 ft. dia. mound of stone, 3 ft. high with a 3" brass cap projecting 12" above the mound of stone and mkd. "T25S R1W S36 R1E S31 T25½S R1E S31 1980 LS 536".