

TOWNSHIP 25½ RANGE 01E POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Cor. Secs. 32, 33; 4 & 5; T26-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9546)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 4, 5, 32, & 33, with brass cap mkd

T25½S R1E  
S 32 | S 33  
S 5 | S 4  
T26S  
1928

from which

- A fir, 7" dia., bears N.7°E., 36 lks., mkd: T25½S R1E S33 BT.
- A fir, 13" dia., bears S.68°E., 41 lks., mkd: T26S R1E S4 BT.
- A fir, 12" dia., bears S.75°W., 19 lks., mkd: T26S R1E S5 BT.
- A fir, 12" dia., bears N.70°W., 52 lks., mkd: T25½S R1E S32 BT.