

TOWNSHIP 25½ RANGE 01E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor. Secs. 33, 34; 3 & 4 T26-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9544-5)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 3, 4, 33, & 34, with brass cap mkd

T25½S R1E  
S 33|S 34  
S 4|S 3  
T26S  
1928

from which

- A fir, 4" dia., bears N.43°E., 17 lks., mkd: T25½S R1E S34  
BT.
- A fir, 5" dia., bears S.76°E., 12 lks., mkd: T26S R1E S3  
BT.
- A fir, 4" dia., bears S.17°W., 8 lks., mkd: T26S R1E S4  
BT.
- A fir, 4" dia., bears N.41°W., 15 lks., mkd: T25½S R1E S33  
BT.