

TOWNSHIP 25½ RANGE 01E POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Township Corner

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9540)

-----

Set an iron post, 3 ft. long, 3" in dia., 27" in the ground, for the cor. of Tps. 25½ and 26 S., Rs. 1 and 2 E., with brass cap marked,

T25½S	
R1E	R2E
<u>S 36</u>	<u>S 31</u>
S 1	S 6
T26S	
1928	

from which

- A fir, 8" dia., bears N.43°E., 27 lks., mkd: T25½S R2E S31 BT.
- A fir, 9" dia., bears S.45°E., 16 lks., mkd: T26S R2E S6 BT.
- A fir, 9" dia., bears S.23°W., 18 lks., mkd: T26S R1E S1 BT.
- A hemlock, 5" dia., bears N.81°W., 29 lks., mkd: T25½S R1E S36 BT.