

TOWNSHIP 25½ RANGE 02E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION W C Secs. 33, 34; 3 & 4 T26-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9638-9

Point for cor. falls on face of steep sloping rock, impracticable to set cor.

At point 42 lks. S of true cor. point, set an iron post, 3 ft. long, 2" dia., 18" in the ground, to bed rock, and in mound of stone, 3 ft. base, for witness cor. to the cor. of secs. 3, 4, 33, & 34, with brass cap mkd.

W C
T25½S | S2E
S33 | S34
S 4 | S 3
T26S
1930

from which

- A fir, 14" dia., bears N.11½°E., 103 lks., mkd: T25½S R2E S34 BT.
- A fir, 13" dia., bears S.65½°E., 70 lks., mkd: T26S R2E S3 BT.
- A fir, 12" dia., bears S.24°W., 65 lks., mkd: T26S R2E S4 BT.
- A fir, 12" dia., bears N.24°W., 129 lks., mkd: T25½S R2E S33 BT.