

TOWNSHIP 25½ RANGE 03E POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Cor. Secs. 32, 33; 4, & 5 T26E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9745)

-----  
Set an iron post, 3 ft. long, 2" dia., 20" in the ground, to bed rock, and in a mound of stone to the top, for cor. of secs. 4, 5, 32, & 33, with brass cap mkd:

T25½S R3E  
S32 S33  
S 5 S 4  
T26S  
1931

from which

- A fir, 30" dia., bears N.56°E., 52 lks., mkd: T25½S R3E S33 BT.
- A fir, 48" dia., bears S.22°E., 182 lks., mkd: T26S R3E S4 BT.
- A fir, 40" dia., bears S.22°W., 37 lks., mkd: T26S R3E S5 BT.
- A fir, 8" dia., bears N.58°W., 88 lks., mkd: T25½S R3E S32 BT.