

TOWNSHIP 25½ RANGE 03E POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Cor. Secs. 35, 36; 1 & 2 T26S R3E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman under Special Instr. dated Dec. 27, 1920, Group No. 64; surveyed Aug. 1930/June 1931 - (DCSO records Vol. 23 Page 9749)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 1, 2, 35, & 36, with brass cap mkd:

T25½S R3E  
S35 S36  
S2 S1  
T26S  
1931

from which

- A fir, 18" dia., bears N.10°E., 77 lks., mkd: T25½S R3E S36 BT.
- A fir, 16" dia., bears S.18°E., 228 lks., mkd: T26S R3E S1 BT.
- A fir, 20" dia., bears S.55°W., 45 lks., mkd: T26S R3E S2 BT.
- A fir, 12" dia., bears N.30°W., 10 lks., mkd: T25½S R3E S35 BT.

Kristian DeGroot, PLS 1941 - For: USFS - Crew Les Fanning, Matt Dixon, & Aaron Fanning - March 1998 - C.S. File 65/20-9

-----  
Found - 2" O.D. iron pipe, firmly set, projecting 8" above the ground with a 2½" brass cap properly stamped. GLO 1930

34" Fir bears N.10°E., 50.8 ft with a healed blaze. 1931

22" Fir bears S.18°E., 150.5 ft. with illegible scribe marks visible on a partially healed blaze.

A root hole bears S.55°W., 30.4 ft.

12" Fir snag bears N.30°W., 6.6 ft. with illegible scribe marks visible on a partially healed blaze.

New BTs- 12" Fir bears N.61°W., 19.4 ft. scribed: "T25½S R3E S35 BT" on a double blaze with a brass washer stamped "PLS 1941" nailed into the lower face.

13" Fir bears S.17°W., 6.8 ft. scribed: "T26S R3E S2 BT" on a double blaze with a brass washer stamped "PLS 1941" nailed into the lower face.

Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.