

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 100133

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only; T26-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4070)

-----

Set a conglomerate stone 18x12x12 ins., 12" in the ground for ¼ sec. cor. marked ¼ on W. face, from which  
A Fir 30" dia., bears S.39°E., 8 lks. dist. mkd. ¼ S31 BT.  
A Fir 10" dia., bears S.64°W., 19 lks. dist. mkd. ¼ S36 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9520)

-----

Intersect the old ¼ sec. cor., established for secs. 31 and 36, which is a conglomerate stone 16x12x9 ins. above ground, marked ¼ on the W. face. I change this cor. to refer to sec. 36 only, obliterating the scribe marks on the SE. BT.  
Alongside of old cor. stone, SET an iron post 3 ft. long, 1" dia., 27" in the ground, for the ¼ sec. cor. of sec. 36 only, with brass cap mkd. ¼ S 36|  
1928

from which  
A Fir 33" dia., bears S.39°E., 8 lks. dist. mkd. ¼ S31 BT.  
(Old bearing tree)  
A Fir 14" dia., bears S.64°W., 19 lks. dist. mkd. ¼ S36 BT. (Old bearing tree)  
A Fir 10" dia., bears N.20°W., 19 lks. dist. mkd. ¼ S36 BT