

PRIMARY CORNER DESCRIPTION Sec. Cor. 25 & 36 only (East); T26-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4070)

-----  
 Set a conglomerate stone 12x10x5 ins., 8" in the ground for cor. of secs. 25, 30, 31 and 36 marked with 5 notches on N. and 1 notch on S. edge, from which  
 A Fir 20" dia., bears N.72 3/4°E., 102 lks. dist. mkd. T26S R1E S30 BT.  
 A Fir 12" dia., bears S.28°E., 40 lks. dist. mkd. T26S R1E S31 BT.  
 A Fir 8" dia., bears S.35°W., 33 lks. dist. mkd. T26S R1W S36 BT.  
 A Fir 20" dia., bears N.53°W., 14 lks. dist. mkd. T26S R1W S25 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9521-22)

-----  
 Intersect the old cor. of secs. 25, 30, 31 and 36, which is a conglomerate stone 10x5x5 ins. above ground, marked with 5 notches on the N. and 1 notch on the S. edge. I change this cor. to refer to secs. 25 and 36 only, obliterating the scribe marks on the NE. and SE. bearing trees. Alongside of old stone cor., SET an Iron post 3 ft. long, 2" in dia., 27" in ground, for the cor. of secs. 25 and 36 only, with brass cap marked:

T26S		T26S
S 25		
		S 31
S 36		
R1W		R1E
		1928

from which  
 A Fir 24" dia., bears N.72 3/4°E., 102 lks. dist. mkd. T26S R1E S30 BT. (Old BT)  
 A Fir 16" dia., bears S.28°E., 40 lks. dist. mkd. T26S R1E S31 BT. (Old BT)  
 A Fir 12" dia., bears S.35°W., 33 lks. dist. mkd. T26S R1W S36 BT. (Old BT)  
 A Fir 24" dia., bears N.53°W., 14 lks. dist. mkd. T26S R1W S25 BT (Old BT)