

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 100233

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only; T26-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4071)

Set a basalt stone 12x8x6 ins., 8" in the ground for ¼ sec. cor. marked ¼ on W. face, from which

A Fir 20" dia., bears S.68°E., 25 lks. dist. mkd. ¼ S30 BT.

A Cedar 30" dia., bears N.78°W., 25 lks. dist. mkd. ¼ S25 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9522)

Intersect the ¼ sec. cor. established for secs. 25 and 30, which is a basalt stone, 14x8x4 ins. above ground, marked ¼ on W. face, I change this cor. to refer to sec. 25 only, obliterating the scribe marks on the SE. bearing tree.

Alongside of old stone cor., SET an iron post 3 ft. long, 1" in dia., 27" in the ground, for the ¼ sec. cor. of sec. 25 only, with brass cap marked: ¼ S25|
1928

from which

A Fir 24" dia., bears S.68°E., 25 lks. dist. mkd. ¼ S30 BT (Old BT)

A Hemlock 12" dia., bears S.66°W., 130 lks. dist. mkd. ¼ S25 BT.

A Cedar 30" dia., bears N.70°W., (not N.78°W.) 25 lks. dist. mkd. ¼ S25 BT. (Old BT)