

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only; T26-1W

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4072)

Point for ¼ sec. cor. falls on a basalt rock in place 5x10x8 ins. above ground on which I cut a cross (X) at exact cor. point, and mark ¼ W of cross, from which

The perpendicular face of a basalt rock, 5 ft. high bears S.13½°E., 8 lks. dist. mkd. with a cross (X) at exact bearing point B O ¼ S 19.

A Madrone 5" dia., bears S.57°W., 46 lks. dist. mkd. ¼ S24 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9524)

Intersect the old ¼ sec. cor., established for secs. 19 and 24, which is basalt stone 5x10x8 ins. above ground with the old marks weathered off. I change this cor. to refer to sec. 24 only, destroying the marks on the SE. bearing object.

Alongside of old cor. stone, SET an Iron post 3 ft. long, 1" dia., 27" in the ground for the ¼ sec. cor. of sec. 24 only, with brass cap marked: ¼ S24|
1928

from which

The perpendicular face of a basalt rock 5 ft. high bears S.13½°E., 8 lks. dist. mkd. with a cross (X) at exact bearing point, B O ¼ 19 (destroy)

A fallen Madrone 5" dia., bears S.57°W., 46 lks. dist. mkd. ¼ S24 BT. (Old BT)

A Fir 12" dia., bears S.20°W., 182 lks. dist. mkd. ¼ S24 BT.

A Madrone 5" dia., bears N.20°W., 83 lks. dist. mkd. ¼ S24 BT.