

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 100473

PRIMARY CORNER DESCRIPTION Sec. Cor. 12 & 13 only (East); T26-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4074)

Set a slate stone 16x6x4 ins., 11" in the ground for cor. of secs. 7, 12, 13 and 18, marked with 2 notches on N. and 4 notches on S. edge, from which

A Fir 12" dia., bears N.39½°E., 74 lks. dist. mkd. T26S R1E S7 BT.

A Fir 6" dia., bears S.68°E., 28 lks. dist. mkd. T26S R1E S18 BT.

A Fir 12" dia., bears S.80°W., 84 lks. dist. mkd. T26S R1W S13 BT.

A Fir 12" dia., bears N.8°W., 40 lks. dist. mkd. T26S R1W S12 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9528)

Intersect the old cor., established for secs. 7, 12, 13 and 18, which is a point determined from three of the original trees. This cor. will hereafter refer to secs. 12 and 13 only. At exact cor. point. SET an Iron post 3 ft. long, 2" dia., 27" in ground, with brass cap mkd.

T26S	T26S
<u>S12</u>	S18
S13	
R1W	R1E
	1928

from which

A Fir 16" dia., bears N.39½°E., 74 lks. dist. mkd. T26S R1E S7 BT. (destroy marks)

A Fir 6" dia., bears S.68°E., 28 lks. dist. mkd. T26S R1E S18 BT. (destroy marks)

No trace of old SW. bearing tree.

A Fir stump 12" dia., bears N.8°W., 40 lks. mkd. T26S R1W S12 BT. (Old BT)

Raise a mound of stone with a 4 ft. base, 2 ft. high S.40°W., 10 lks. dist., from cor., as no bearing trees were available and the ground was too steep to raise the mound of stone W. of cor.

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 16, 1971 - C.S. File 54/94-108

Found - 1928 GLO brass cap, properly mkd., firmly in ground at proper dist. 6.85 chs. (752.10 ft.) from closing cor. (Cont. Next Page)

TOWNSHIP 26 RANGE 01E POINT IDENTIFIER # 100473

PRIMARY CORNER DESCRIPTION Sec. Cor. 12 & 13 only (East); T26-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Also found possible rock mound S.60°W., (Rec. S.40°W.) 6.6 ft. No other means of identification.

New Accessories:
11" D.Fir N.12°W., 37.8 ft. scribed T26S R1W S12 CS BT.
PK nail in outcrop South 14.4 ft. PK nail approx. 8.0 ft. above ground on NW. end of rock.
Rock outcrop bears South 14.4 ft. Set PK nail. Rock approx. 8.0 ft. high, 8.0 ft. long. Cor. on steep SW. slope in opening on SW. edge of brash patch.

2