

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12, (East); T26-1W

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4975-76)

-----  
Point for cor. of secs. 1, 6, 7 and 12, falls on the N. face of a basalt rock 4 x 4 x 3 ft., on which I cut a cross (X) at exact corner point, with 1 notch N. and 5 notches S. of cross, from which

- A Fir 24" dia., bears N.25°E., 34 lks. dist. mkd. T26S R1E S6 BT.
- A Fir 24" dia., bears S.54°E., 53 lks. dist. mkd. T26S R1E S7 BT.
- A Cedar 24" dia., bears S.88°W., 59 lks. dist. mkd. T26S R1W S12 BT.
- A Hemlock 24" dia., bears N.30°W., 74 lks. dist. mkd. T26S R1W S1 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 22 Page(s) 9530)

-----  
Intersect the old cor., established for secs. 1, 6, 7 and 12, which is a basalt rock, 4x4x3 ft. marked with a cross (X) at exact cor. point, and 1 notch N. and 5 notches S. of cross. I change this cor. to refer to secs. 1 and 12 only, obliterating the scribe marks on the NE. and SE. bearing trees, from which the original bearing trees:

- A Fir snag 24" dia., bears N.25°E., 34 lks. mkd. T26S R1E S6 BT.
- A Fir snag 24" dia., bears S.54°E., 53 lks. mkd. T26S R1E S7 BT.
- A Cedar snag, 18" dia., bears S.88°W., 59 lks. mkd. T26S R1W S12 BT.
- A Hemlock snag 18" dia., bears N.30°W., 74 lks. dist. mkd. T26S R1W S1 BT.